TWISTER TM



Twister™ Hybrid Red, floor pad

Technical data sheet

Product description:

Nonwoven pad made from PET impregnated with microscopic diamonds bound in resin. Diamond abrasive applied on one side of the pad. Thickness of the pad is approximately 13 mm (1/2 inch). The pad is shaped like a star with varied outer diameter.

Intended use:

The pad is developed to be used for deep cleaning and honing of stone and stone-like floors. The pad requires a Twister Hybrid Holder (sold separately) and is used in combination with Twister Hybrid Tool Red and Black.

Durability and limitations:

Lifespan up to 10 000 m² (optimal use).

Sizes:

13"-18",20" and 21"

Product Characteristics:

Pad color: White. The impregnation is red.

Marking: All markings are on one side of the pad (opposite side to the diamond impregnations). The markings consist of "Twister™" "Red", the dimension in inches and "Machine Side" Centre hole: Pre-cut at 3 1/4"

(82,6mm)

Typical properties:

Property	Value	Test Method
O.D Dimension	Designated size +/- 1/16 inch (1,6 mm)	
Thickness	10 mm +/- 10%	D5736-95
Weight	430 g/m ² +/- 10% (without impregnation)	D6242-98
Fiber type	PET	
Average tensile strength	65 lbs/2 inch	D461.12-93
Recycle content of packaging	At least 35% post- consumer recycled material.	

Directions for use:

- Dry mop the floor. Dry mopping improves the honing and deep cleaning result.
- Mount the Twister™ Hybrid Red pad and the Twister Hybrid Tool on the Twister Hybrid Holder. Mount the holder on the machine pad holder.
- Hone the floor

Maintenance of pad:

Rinse the Twister™ pad thoroughly with water after each use. This ensures the proper function of the Twister™ Hybrid pad.

Packaging:

2 Pads/package.

Special Features:

Honing and deep cleaning method using only water in the cleaning. No chemicals required.

Intended for stone and stone-like floors.

Twister™ Hybrid Red is used for renovation of stone stone-like floors. The honing is to be followed by Twister™ procedure.

Web: www.twisterpad.com